#### **TECHNICAL SPECIFICATIONS** & **INFORMATION**

#### THEATER, DANCE & MEDIA

FARKAS HALL | 12 HOLYOKE ST. CAMBRIDGE MA 02138 | 617.496.2796 | TDM@FAS.HARVARD.EDU

<u>Stage</u>

Stage Dimensions: Theater dimensions:

Mainstage - 60'0" wide x 28'9" deep. Proscenium arch - 41'6" wide x 28'0" tall.

Load gallery on SR wall, X-Over gallery located at the US wall, and Utility

Gallery on SL wall.

Grid Steel is approximately 43'6.

Stage Floor, from top to bottom: 3/8" paintable MDF deck, %" black-painted Masonite,

Gemthane finish on a 3/4" maple plank T&G,

2 layers of 5/8" plywood, 2x4 sleepers on neoprene pads.

No traps.

Access/Crossover: From SL to SR, through hallway on LL2

Access to front of theatre via building hallways.

Rigging: Counterweight Fly System:

43 line sets, on 6" centers

SL and SR tabs are operated on LS #49 & #50.

Length of Batten = 42'.

1" brick = 18 lbs, 2" brick = 36 lbs

Support Areas

Loading Dock The loading dock is located in the rear of the building (65 Rear Mount Auburn),

accessed through a small alleyway, vehicle must be 8' wide or less and no more than 11' tall. Access to theater is via the stage loading door located at the rear of the building. Stage loading door is 12' above stage deck, 6'-0"w x 9'-0"h. Access to a elevator from ADA ramp in rear of building, opening 4'6"w x 8'6" H,

elevator cab 8'6"w x 9'0"h x 4'6"d.

Production Room A small office/meeting room is available

Green Room 8'6' x 16', located on same floor as stage. Closed circuit video monitor,

page/relay monitor.

Dressing Rooms Two chorus-style rooms, 14' x 16', with 10 makeup stations, restrooms, and

showers

Wardrobe Area Small wash room containing an industrial steam iron, ironing board, washer

and dryer, and six rolling racks (6'x4'6") available

Quick Change booths As requested, see Production Manager

Shop Space Located on LL2. Access stage from stairs, elevator, or pit lift. Access to tools by

permission of Production Manager.

#### THEATER, DANCE & MEDIA

FARKAS HALL | 12 HOLYOKE ST. CAMBRIDGE MA 02138 | 617.496.2796 | TDM@FAS.HARVARD.EDU

Draperies (H x W, feet)

Borders 6 - 12' x 41', Black 24oz. Charisma

Legs 12 - 23' x 8'6", Black 24oz. Charisma

Tabs 10 - 23' x 4', Black 24oz. Charisma

Cyc 1 - 25' x 41', White Seamless 100% cotton

Bounce 1 - 25' x 41', White Seamless 100% cotton, w/some damage

Scrim 1 - 23' x 41', Black sharkstooth

1 - 23' x 41', White sharkstooth (minor tear, top SR corner)

Traveller Curtains 2 - 23' x 21', Black 24oz. Charisma

House Curtain 1 - 35' x 66'3", Desert Shadows 24oz. Charisma (Austrian, 50%)

Lighting

Power 2 - 120/208V 3-phase 100A company switches on SL & SR.

1 - 120/208V 3-phase 400A company switch on SL.

2 - Convenience Power panels (4 – 20A twistlock, 8 – 20A edison duplex, 8 – 20A

stagepin)

Dimmers 288 - 2.4kW ETC Sensor D20, dimmer per circuit

33 - 2.4kW ETC Sensor R20, non-dim per circuit

Control ETC EOS, monitors, fader wing available.

Designer Remote also available upon request.

House Lights Control locations at SR wall panel, SL portable stage manager's rack, and in

control booth.

LX Equipment Inventory Ellipsoidal Reflector Spots	17 - 30 - 92 - 45 -	All connectors are 2PG, unless indicated otherwise ETC Source Four 750W bodies 90° S4 tubes 70° S4 tubes 50° S4 tubes 36° S4 tubes 26° S4 tubes 19° S4 tubes 14° S4 tubes
Enhanced Definition Tubes		50° S4 tubes 36° S4 tubes 26° S4 tubes 19° S4 tubes
PARs	56 -	ETC Source Four PAR 750w (VNSP, NSP, MFL, WFL)
CYC Lights	5 - 5 -	ETC MultiPAR 750w, (3 cell/circuit, 4 circuit, 8') Lectrosonic MR-16 Strip 75w (20 cell/circuit, 4 circuit, 8')
Color Mixing Instruments		See production staff for availability.
Cable		5' stagepin 10' stagepin 25' stagepin 50' stagepin 2-fers stagepin 10' 6-circuit multicable (Socoplex) 50' 6-circuit multicable (Socoplex) 75' 6-circuit multicable (Socoplex) 6-circuit multicable, staggered breakout (Socoplex) 6-circuit multicable, straight breakout (Socoplex) F Edison to M Stage Pin adapters F Stage pin to M Edison adapters 15' Edison 25' Edison 50' Edison 100' Edison Edison 3-fers 25' E-Cable (multi-socket)
DMX – 5-pin	5 - 9 - 6 - 1 - 1- 3 -	5' 10' 25' 50' 75' 100'

Source 4 Accessories 30 - ETC S4 Top Hats

5 - ETC 7.5" Top Hats

55 - ETC S4 PARs Barndoors

25 - ETC S4 Gel Extenders

7 - ETC S4 Iris

22 - ETC S4 Donuts

31 - ETC Size "A", Template Holders

25 - ETC Size "B", Template Holders

4 - ETC Size "B", Glass Holder

Miscellaneous Hardware 48 - 18" Single Sidearms

8 - 10' Boom pipe Booms

8 - 50 lbs. boom base

Sound		
Mixer/Console		Yamaha QL1 Dante network-enabled XLR - 16 inputs/8 outputs
Network	2 -	RiO1608D Stage Boxes
Stock PA		Left & Right Mains – Renkus Heinz TRX 81 Center Main – EV EVI-15 Subwoofer – Renkus Heinz BPS12-12 Center Rail House Fills – 6 @ QSC AD-S32T Rear of House Surround – 2 @ JBL Control 25
Control Room		Equipment racks Patch bay Power sequencer
Amplifiers		Crown D-75A – Booth Speakers Left & Right QSC PowerLight 2 (2chan) – Mains Left & Right QSC PowerLight 2 (2chan) – Subwoofer, bridged QSC PowerLight 2 (2chan) – FX 1 & 2 (unassigned) QSC PowerLight 2 (2chan) – FX 3 & 4 (unassigned) Crown K1 (2chan) – Center Main & spare Crown K1 (2chan) – Center Rail House Fill Left & Right Crown K1 (2chan) – Spare (unassigned)
Addl' Speakers	2 - 2 - 2 - 2 - 2 -	JBL Control 30 - See production staff for status JBL Contol 1 Renkus Heinz TRX 82, w/hanging yokes Renkus Heinz TRX 82, w/o hanging yoke EAW JF80 EV ELX112P Powered Speakers, w/stands EV ELX118P 18" Powered Subwoofer
Playback/EFX	2-	MacPro Tower w/QLab4 Saffire Pro40 USB Interface Lexicon MX200 FX Processor
Microphones	3 - 16 - 4 - 5 - 1 -	Shure ULX SM58 wireless handheld Shure ULX wireless beltpack Shure SM58 wired Shure SM57 wired Shure Beta 52
		1
Comm	7 - 3 - 6 - 1 -	ClearCom wired beltpacks w/headsets ClearCom wireless beltpacks Wall stations in green room/dressing rooms House Mic
Comm  In-Ear Monitors Assited Listening Devices	3 - 6 -	ClearCom wireless beltpacks Wall stations in green room/dressing rooms

<u>Media</u>		
Theater Projection		Christie DMU951 8500 Lumen Projector Crestron Presentaton System, DMPS3-4K-150-C Input locations: House mix position, stage right, control booth 16x9 Portable Projection Screen
Additional Projectors	3 – 2 –	BenQ #MW526 - Throw 1.5-1.65, 3200 Lumens BenQ #HT1085ST – Short throw .6983, 2200 Lumens BenQ #MW632 – Throw .7287, 3200 Lumens
Computers	3 -	Mac Mini w/Qlab4
Displays	2 - 2 -	Acer 18.5" Monitor, #V196HQL Acer 27" Monitor, #KA27OH Samsung LED 40" Display, #UN40J5200AFXZA
Accessories	2 -	HDMI 1x4 Splitter Kramer 4x1 HDMI Matrix Switcher Kramer 4x2 HDMI Matrix Switcher HMDI to AV converter Matrox Triplehead 2Go, #T2G.DP3D.IF BlackMagic Intesity Shuttle, #2590823 BlackMagic Decklink Recorder Video Capture Rig Extron DTP/DVI Units, Rx/Tx Enttec USB Pro DMX Adapter